
INSTRUCTION MANUAL





QAZQA

FittinQ B.V. Smaragdweg 52, 5527 LB Hapert, The Netherlands www.qazqa.nl


104500/104501/104502/104503


5W+2W LED incl. LED Board: QL7001040/QL7001039 220-240V~50Hz





(DE) Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse D	QR	EAN
 (EN) This product contains a light source of energy efficiency class D (FR) Če produit comprend une source de lumière de classe d'efficience énergétique D (NL) Dit product bevat een lichtbron van energie-efficiéntieklasse D (PL) Produkt ten zawiera źródło światła o klasie efektywności energetycznej D (NO) Dette produktate inneholder en lyskilde i energieffektivitetsklasse D (DK) Dette produkt ten dolder en lyskilde ai energieffektivitetsklasse D (SE) Denna produkt innehôlder en lyskilde i energieffektivitetsklasse D (SE) Denna produkt innehôlder en lyskilda i energieffektivitetsklasse D (FI) Tämä tuote sisältää energiatehokkuusluokan Dvalonlähteen (IT) Questo prodotto contiene una sorgente luminosa della classe di efficienza energetica D (ES) Este producto contiene una sorgente luminosa della classe di efficienzia D (CZ) Tento výrobek obsahuje světelný zdroj třídy energetické účinnosti D (PT) Este produto contém de luz da classe de eficiencia energética D (GR) Aucé to rxpolóv rapitýcu μα φωτεινή πηγή ενεγρειαχής απόδοσης κλάσης D (SK) Tento výrobok obsahuje zdroj svetla triedy energetickej efektivity D 		104500: 8718881128448 104501: 8718881128458
 (DE) Disses Produkt enthält eine Lichtquelle der Energieeffizienzklasse F (EN) This product contains a light source of energy efficiency class F (FR) Ce produit comprend une source del lumière de classe d'efficience énergétique F (NL) Dit product bevat een lichtbron van energie-efficient/klasse F (PL) Produkt ten zawiera źródio światła o klasie efektywności energetycznej F (NO) Dette produkt indeholder en lyskilde i energieffektivitetsklasse F (DK) Dotte produkt indeholder en lyskilde i energieffektivitetsklasse F (FK) Ce produkt indeholder en lyskilde a energieffektivitetsklasse F (FK) Dette produkt indeholder en lyskilde a energieffektivitetsklasse F (FK) Dette produkt indeholder en lyskilde a energieffektivitetsklasse F (FK) Dette produkt innehåller en ljuskälla i energieffektivitetsklasse F (FK) Dette produkt innehåller en ljuskälla i energieffektivitetsklasse F (FK) Dette produkt ochtiene una sorgente luminosa della classe di efficienza energetica F (ES) Este producto contiene una sorgente luminosa della classe di efficienzi energética F (EZ) Tento výrobek obsahuje světelný zdroj třídy energetické účinnosti F (FT) Este producto contiem uma fonte de luz de laclase de eficiencia energética F (ER) Auró to ropolóv rezpirkezu jud wpreyreuxify ardbörong khádong c hádong c filomet F (FK) Tento výrobok obsahuje zdroj svetla triedy energetickej efektivity F 		104502:8718881128462 104503:8718881128479





FittinQ B.V. Smaragdweg 52, 5527 LB Hapert, The Netherlands www.gazga.nl



SAFETY INSTRUCTION

Please study the instruction manual and below information carefully before installing or using this product. Please keep this user manual for further reference

- 1. The luminaires may only be installed by authorized and qualified technicians according the valid regulations for electrical installation.
- 2. Maintenance of the luminaires is limited to their surfaces. During maintenance no moisture can come into contact with any areas of the terminal connections or voltage control parts.
- 3. The electrical supply must be switched off at the outset, preferably by means of a switch in the distribution box, before any installation, maintenance or repair work is undertaken.
- 4. Exterior lighting must not be installed during rain.
- 5. Take account of the minimal separation distance from other objects and the room required around the fitting.
- 6. If in any doubt, consult a professional, taking local installation requirements into account. Some countries stipulate that lighting may be installed only by registered installers.
- 7. Clamping screws in electrical connections must be adequately tightened. This is particularly the case with 12V low voltage conductors.
- 8. When replacing a halogen lamp, wait for it to cool, for a minimum of 5 minutes.
- 9. Clean with a clean, dry cloth or brush, use no solvents or abrasives. Avoid dampness on all electrical components
- 10. Take account of all available technical information.
- 11. Take note of the symbols when connecting wires: ⊕ = Earth
- N = Neutral L = Live
- 12. Meaning of symbols:

	For indoor use only, where direct contact with water is impossible
	This icon indicates the level of water-proof and dust-proof
	Protection Class I: the fitting must be earthed
	Protection Class II: the fitting is doubled insulated and does not require earthing
	Protection Class III: the fitting is low voltage
	Minimum distance from lighted objects (meters)
	Only the self-shielded halogen lamp should be used with the luminaire
8mm	Strip the wire to the indicated length (mm);different items require different length
3x min.0,75mm ²	Connect using the specified cable; different items require different cables
Max.ø50mm Gu10 2xMax.50W	The type of lamp and maximum size and wattage indicated in each lighting unit must not be exceed; different items require different kind of light sources with different bulb icons
220-240V~ 50Hz	The armature is designed to work only with the indicated voltage. Different items require different working voltage.
	The luminaire can be used in combination with a dimmer
	The luminaire can be dimmed by wall switch
Light Angle 55° 35cm²	The reference light angle and light space of the luminaire
	This luminaire cannot be disposed together with normal domestic waste in standard rubbish can, but you have to bring it to a staging area for electrical waste

FittinQ B.V. Smaragdweg 52, 5527 LB Hapert, The Netherlands www.qazqa.nl

ϙϥΖϘΑ