

## 45447 Using Manual



## Using instruction

For undergrourd & underwater lamp

- Must be clear all parts when you fix the sealing plastic ring, glass and cover, Avoiding to seep the water in the lamp and damage the lighting fixtures. The screw should be all together one time and each one screw recycl four times, not one time srew.
- 2. The cable diameter size same as waterproof interface size of the sealing plastic stopper, pls do not over power to jundied the stopper, enough is Ok, otherwise, will be more tighten and damage the plastic stopper, infect waterproof function. You should be pull the cables more times after fixing the plastic stopper, check it tighten or not.
- 3. The top of the house is same lever the earth, not lower earth...
- 4. Choose waterproof junction box, prevent water vapor from the jacket and infiltrate to the lamp body, after connecting, pls use epoxy resins to seal the whole junction box.
- 5. The lamp source light on one hour before you cover the glass, and then tighten the cover. It is convenience eliminate the humidity in the lamp. Otherwise, the humidity be heated and became the bead on the glass, the bead drop on the lamp source and make the damage.
- When you are cover up the underground lamp, pls put grit on the bottom, thickness more than 30CM.
- 7. Products are passed IP65 and more grade, no need to glass glue or epoxy resins again, If you do it again, pls do remember that do not open the cover to make the glue or epoxy resins in side, make it outside place which you are not reassurance it! Otherwise, will be seep the water in side of lamp.

Pls read the using introduction before fixing the lamp.

